

**TECHNICAL SPECIFICATION**  
**EKEBOL WHEEL LIFT MODELS**  
**OPTIONS**

(date of issue: 19 Aug 2019 – Rev C)

<b>Option Code</b>	<b>Description</b>
TW-OPT1A	(Available on TW-3 only!) DELETE Wheel lift hydraulic wheel clamping system and replace with square T-bar and manually removable L-bars
TW-OPT1B	(Available on TW-3 only!) Hydraulic Recovery Boom
TW-OPT1C	(Available on TW-3 only!) DELETE Wheel lift hydraulic wheel clamping system and replace with manual cradle arrangement
TW-OPT2A	Fully enclosed body with built in tool boxes, and full width high light rack.
TW-OPT2B	Automatic "flip-down" light rack behind cab.
TW-OPT4A	(Available on TW-2 only!) "Tilt on the Run" system.
TW-OPT5A	(Available on TW-3 only!) One hydraulic worm drive winch (3.6 tonne single line pull capacity) mounted on lifting boom
TW-OPT5A-5	(Available on TW-3 only!) One hydraulic worm drive winch (5.4 tonne single line pull capacity) mounted on lifting boom
TW-OPT5B	(Available on TW-3 only!) One hydraulic planetary drive winch (5.0 tonne single line pull capacity) mounted on lifting boom
TW-OPT5C	(Available on TW-3 only!) Two hydraulic worm drive winches (each with 3.6 tonne single line pull capacity) mounted on lifting boom
TW-OPT5D	Pneumatic operated dog-clutch on the winch(es). Truck must have air brake system
TW-OPT5E	(Available on TW-2 only!) One hydraulic worm drive winch (3.6 tonne single line pull capacity) mounted behind the cab. Available on TW-2 only
TW-OPT6B	Two high visibility twin spinner Blaze Bars mounted on the light rack
TW-OPT6B-LED	Two high visibility twin spinner LED Blaze bars mounted on optional high mounted headboard
TW-OPT6C	Two adjustable work lights mounted on the body
TW-OPT6C-1	One adjustable work light mounted at the rear of the unit
TW-OPT6D	Integrated Starter Cable kit with 7m cable & isolator switch
TW-OPT7A	Two sliding fork-holders and 2 pairs of forks
TW-OPT7B	Removable towing adaptor, with 50mm ball for towing of trailers
TW-OPT7C	Removable towing adaptor, with pintlehook and ball for towing of trailers
TW-OPT7D	Removable towing adaptor, with pin type coupling
TW-OPT8A	Wheel lift and optional body painted in 2-pack enamel in customer's choice of colours (solid colours only)

# **EKEBOL**

**Tough - Reliable - Built to Last**

## **NOTES**

- a. Capacity Statement:
  - i. Body Capacity: The rated capacity for the tilt tray body or recovery equipment as shown in the quote above is the rated capacity of the tray body or recovery equipment ONLY. It is not the legal load carrying capacity of the finished truck and body combination, which is dependent on the truck make/model/axle tare weights and options fitted. The customer must confirm the estimated legal load carrying capacity of the truck & body combination prior to order placement.
  - ii. Winch Capacities. Winch capacities are quoted per winch manufacturer standard practice. This is the maximum pulling force on a single line at rated oil pressure, rated oil flow rate and with the winch rope only on the bottom layer of the winch.
- b. **Tow adaptors are for recovery/emergency towing only – not to be used for continuous highway towing.**
- c. Ekebol Pty Ltd is continually striving to improve and update our product range. We reserve the right to change materials and specification without notice. Specifications are correct at the time of printing but may change without notice.